

Mini Dry Bath

MiniHCL100/MiniHC100/MiniH100

Portable and option to power by automobile power adapter

Features

- Mini, lightweight, safe with LCD display
- Digital control over both temperature and time
- Built-in user recalibration function guarantees long term temperature accuracy
- Overheating protection
- Optional cooling function
- Interchangeable blocks for a wide variety of test tube sizes
- Mini HCL100 with hot lid to prevent water condensing on the tube cap



Applications

Useful for rapid and uniform heating of biological samples in applications like preservation, denaturation of nucleic acids and proteins, and many other applications.

Specifications	Mini HCL100	Mini HC100	Mini H100
Display	LCD	LCD	LCD
Temperature setting range[°C]	0-100	0-100	25-100
Temperature range [°C]	Room temperature-23~100	Room temperature-23~100	Room temperature+5~100
Temperature control accuracy[°C]	±0.5	±0.5	±0.5
Temperature display accuracy[°C]	0.1	0.1	0.1
Minimum time taken for heating(25°C+100°C)	≤20min	≤20min	≤20min
Minimum time for cooling(20°C-0°C)	≤25min	≤25min	-
Max. Heating Rate	8°C/min	8°C/min	6.5°C/min
Max. Cooling Rate	3°C/min	3°C/min	-
Time setting range	0-999min/0-999sec	0-999min/0-999sec	0-999min/0-999sec
Program Memory	9(2steps for each)	9(2steps for each)	9(2steps for each)
Temperature self-calibration	Support	Support	Support
Error code display	Support	Support	Support
Dimension[WxDxH]	110x162x140mm	110x162x140mm	110x162x140mm
Total Weight [kg]	≤1	≤1	≤1
Voltage,Frequency	100-240V, 50/60Hz or DC12V	100-240V, 50/60Hz or DC12V	100-240V, 50/60Hz or DC12V
Power [w]	60	60	60
Operating temperature[°C]	+10-40	+10-40	+10-40
Operating humidity [% RH]	≤80	≤80	≤80

HB105-S1 /HB105-S2 /HB150-S1 /HB150-S2

Cat.No	18900459	18900460	18900461	18900462	18900463
Block types					
Capacity	30×0.2mL	20×0.5mL	20×1.5mL	20×2mL	12×5mL
Diameter×depth	6.4×15mm	7.85×28.4mm	11×34.7mm	11×34.7mm	16.6×46mm

Cat.No	18900464	18900465	18900522	18900523	18900520
Block types					
Capacity	12×15mL	4×50mL	Dual purpose block,bead bath/water bath Adapt to S1	Dual purpose block,bead bath/water bath Adapt to S2	Aluminum beads
Diameter×depth	16.6×73mm	29.2×73.5mm	95×76×56mm	151×95×62mm	—

Mini HCL100/Mini HC100/Mini H100

Cat.No	18900414	18900415	18900416	18900428
Block types				
Capacity	40×0.2mL	24×0.5mL	15×1.5mL	15×2mL
Diameter×depth	6.4×20 mm	8.2×28.4mm	11.2×31mm	11×31mm

Cat.No	18900417	18900426	18900427
Block types			
Capacity	6×5mL	4×15mL	2×50mL
Diameter×depth	17×31mm	16.4×45mm	29×45mm